

## X-CLEAR AM EAS SYSTEM

The new, black, X-Clear AM EAS system operates at 58 KHz. A full acrylic structure is supported by high-end, thin aluminum profiles. The slim base makes the X-Clear AM one of the thinnest EAS systems in the market today.

The X-Clear AM is easily upgraded with a TCP/IP module which allows to remote connect and service the system. Through high-end software system data can be extracted to one central point.

### Features

Advanced anti noise algorithms

Jammer Alarm

Near Tag Alarm

Silent Alarm through app

System Status

Green Mode

Aisle Identification Light

Relay Output

RGB light

Programmable sound and light

Internet access

Tuning Software

Extended Connectivity

Included

Optional



## Detection range

DR Labels, Supertag Up to 200 cm

Ferrite Tags Up to 240 cm

Detection ranges measured under low electrical noise conditions. Detection ranges under higher electrical noise conditions may decrease. For mono systems, total detection coverage (both sides of the antenna). For dual systems, detection coverage between the antennas.

## Technical specs

Width 442 mm

Height 1527 mm

Depth 27 / 51 mm

Weight 12 kg

Mains 110/220 V

Relay/Inputs/Outputs 1/2/2

Operating temperature Up to 58°C / 185°F

## Product reference

TRX Antenna XS-A2MXC58TRXB

RX Antenna XS-A2MXC58RAB

